



**NYLON HEAVY DUTY CABLE CLAMPS—1/2" WIDE CONTACT AREA**

| Part Number  | Size<br>(Clamping Diam. x<br>Hole Size x Con-<br>tact Length) | C                 |       | H         |      | L                    |       |
|--------------|---------------------------------------------------------------|-------------------|-------|-----------|------|----------------------|-------|
|              |                                                               | Clamping Diameter |       | Hole Size |      | Hole-to-Clamp Length |       |
|              |                                                               | Max               | Min   | Max       | Min  | Max                  | Min   |
| 125167CCN08  | 1/8x.167x.315                                                 | .130              | .120  | .182      | .152 | .330                 | .300  |
| 125203CCN08  | 1/8x.203x.315                                                 | .130              | .120  | .218      | .188 | .330                 | .300  |
| 188203CCN08  | 3/16x.203x.425                                                | .193              | .183  | .218      | .188 | .440                 | .410  |
| 250167CCN08  | 1/4x.167x.410                                                 | .255              | .245  | .182      | .152 | .425                 | .395  |
| 250203CCN08  | 1/4x.203x.410                                                 | .255              | .245  | .218      | .188 | .425                 | .395  |
| 312167CCN08  | 5/16x.167x.500                                                | .317              | .307  | .182      | .152 | .515                 | .485  |
| 312203CCN08  | 5/16x.203x.500                                                | .317              | .307  | .218      | .188 | .515                 | .485  |
| 375167CCN08  | 3/8x.167x.530                                                 | .380              | .370  | .182      | .152 | .545                 | .515  |
| 438203CCN08  | 7/16x.203x.560                                                | .443              | .433  | .218      | .188 | .575                 | .545  |
| 500167CCN08  | 1/2x.167x.595                                                 | .505              | .495  | .182      | .152 | .610                 | .580  |
| 500203CCN08  | 1/2x.203x.595                                                 | .505              | .495  | .218      | .188 | .610                 | .580  |
| 562167CCN08  | 9/16x.167x.606                                                | .567              | .557  | .182      | .152 | .621                 | .591  |
| 562203CCN08  | 9/16x.203x.606                                                | .567              | .557  | .218      | .188 | .621                 | .591  |
| 625203CCN08  | 5/8x.203x.678                                                 | .630              | .620  | .218      | .188 | .670                 | .640  |
| 688203CCN08  | 11/16x.203x.755                                               | .696              | .680  | .218      | .188 | .770                 | .740  |
| 750167CCN08  | 3/4x.167x.780                                                 | .758              | .742  | .182      | .152 | .795                 | .765  |
| 750203CCN08  | 3/4x.203x.780                                                 | .758              | .742  | .218      | .188 | .795                 | .765  |
| 812203CCN08  | 13/16x.203x.815                                               | .820              | .804  | .218      | .188 | .830                 | .800  |
| 875203CCN08  | 7/8x.203x.845                                                 | .883              | .867  | .218      | .188 | .860                 | .830  |
| 1000203CCN08 | 1x.203x.910                                                   | 1.008             | .992  | .218      | .188 | .930                 | .895  |
| 1125203CCN08 | 1 1/8x.203x.970                                               | 1.135             | 1.115 | .218      | .188 | 1.000                | .955  |
| 1250203CCN08 | 1 1/4x.203x1.060                                              | 1.260             | 1.240 | .218      | .188 | 1.075                | 1.045 |
| 1375203CCN08 | 1 3/8x.203x1.125                                              | 1.385             | 1.365 | .218      | .188 | 1.140                | 1.110 |
| 1500203CCN08 | 1 1/2x.203x1.190                                              | 1.510             | 1.490 | .218      | .188 | 1.205                | 1.175 |

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Description</b>                    | A molded nylon component formed into a shape that creates a cylindrical area through which wires or cables may pass. The part holds its shape until manual pressure is applied to the two flat ends to join them together. A hole in the center of the two flat ends allows for a screw to pass through and be fastened with a nut to securely close the clamp once the cables it is to hold are in place. The edges of the two ends are rounded. The size is marked on each clamp. The heavy duty series has a 1/2" wide contact area. |
| <b>Applications/<br/>Advantages</b>   | Designed for heavy duty industrial and commercial applications that involve securing, insulating and routing cable wiring, tubing and fiber optic cable.                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Material</b>                       | Flame Retardant Nylon 6/6                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Continuous Use<br/>Temperature</b> | 220° F                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Melting Point</b>                  | 470° F                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |